

## CNC 150

<b>IP67</b> <b>IK 10 20J xx9</b> CE UK CA 2000 KG MAX 58°C MAX	<b>LED</b>			<b>COL. CODE *</b>		
	<b>W</b>	<b>LM</b>	<b>REAL LM</b>	<b>COL.</b>	<b>CODE *</b>	
	20	2800	2480	600mA	LL136000□	

\* Complete the CODE     OPTIC    S | 12°    M | 24°    L | 32°     LED COLOUR    N | 4000K    3 | 3000K    2 | 2700K

Disponibile su richiesta versione a 24V. | 24V version available on request. | Version 24V disponible sur demande. | Versión de 24 V disponible bajo pedido.

## Accessori | Accessories | Accessoires

### Cavo H05RN-F 2x0,75

**Cavo H05RN-F in Neoprene, sezione 2x0,75. Adatto ad uso esterno.**

Cable type H05RN-F in Neoprene, section 2x0.75. Suitable for outdoor use.

Câble H05RN-F en Néoprène, section 2x0,75. Également adapté à l'usage à l'extérieur.

Cable H05RN-F de Neopreno, sección 2x0,75. Adecuado para el uso al exteriores.

<b>5m</b>	<b>15m</b>
<b>Code</b>	<b>Code</b>
LB1070004	LB1070006
<b>10m</b>	<b>20m</b>
<b>Code</b>	<b>Code</b>
LB1070005	LB1070007



### Armatura da incasso CNC 150


**Armatura da incasso in termoplastico.**

**Thermoplastic recess box CNC 150.**

**Armature à encastrer en matériau thermoplastique CNC 150.**

**Caja de empotrar de material termoplástico CNC 150.**

<b>Col.</b>	<b>Code</b>
-	LB1360001




### Alimentatori CNC 150 in corrente costante

**Drivers in constant current CNC150**

**Alimentations à courant constant CNC 150**

**Alimentadores de corriente constante CNC 150**

<b>N° max</b>	<b>IP</b>	<b>Code</b>
1	20	LB1070063
1 DALI	20	LB1070064
1	67	LB1070112



CNC 150

