











CNC 25 T




IP67 IK 10 20J xx9 CE UK CA 500 KG MAX 65°C MAX	LED			COL.	CODE *
	W	LM	REAL LM		
 24W: Fino ad esaurimento. Until our stock lasts. Jusqu'à épuisement de stock. Hasta el agotamiento del stock.	2	180	Max 148	 500mA-4,8V	 LL119000□□
					 LL119004□□
					 LL119006□□
	2	180	Max 148	 12/24V	 LL119001□□
 LL119005□□					
 LL119007□□					




* Complete the CODE ○ OPTIC M | 30° S | 15° D | Diff. □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K B | Blue

Idoneo per installazione in tubo corrugato standard Ø25 mm. | Suitable for installation in standard Ø 25 mm corrugated duct. | Convient pour une installation dans un tube annelé standard Ø25 mm. | Adecuado para instalación en tubo corrugato estándar Ø 25 mm.

CNC 25 Q

IP67 IK 10 20J xx9 CE UK CA 500 KG MAX 65°C MAX	LED			COL.	CODE *
	W	LM	REAL LM		
 24W: Fino ad esaurimento. Until our stock lasts. Jusqu'à épuisement de stock. Hasta el agotamiento del stock.	2	180	Max 148	 500mA-4,8V	 LL119002□□
					2



* Complete the CODE ○ OPTIC M | 30° S | 15° D | Diff. □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K B | Blue

Idoneo per installazione in tubo corrugato standard Ø25 mm. | Suitable for installation in standard Ø 25 mm corrugated duct. | Convient pour une installation dans un tube annelé standard Ø25 mm. | Adecuado para instalación en tubo corrugato estándar Ø 25 mm.