

CNC 50 T 2.0



IP67 IK 10 20J xx9 ↓ 500 KG MAX CE UK CR 	LED				COL.	CODE *	
	W	LM	REAL LM				
	6,5	694	575	⊗ 24V	LT158200□□ LT15820E□□ LT15820K□□ LT15820W□□ LT15820B□□		
	6,5	694	392	⊗ 24V	LT15820HO□□ LT15820HE□□ LT15820HK□□ LT15820HW□□ LT15820HB□□		

* Complete the CODE OPTIC S | 25° M | 30° L | 50° D | Diff. LED COLOUR N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

Versione Honeycomb non disponibile con ottica D. | Optic D not available for Honeycomb version. | Optique D non disponible pour la version Honeycomb. | La óptica Diff. no está disponible para la versión Honeycomb.

CNC 50 T 2.0 Full Resin



IP69 / IP 67 IK 10 20J xx9 ↓ 500 KG MAX CE UK CR 	LED				COL.	CODE *	
	W	LM	REAL LM				
	6,5	694	252	⊗ 24V	LT158200F□ LT15820EF□ LT15820KF□ LT15820WF□ LT15820BF□		

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

Versione Full Resin: nuova tecnologia di incapsulamento dei led e circuiti elettronici che allunga la durata del prodotto. Presenta vetro diffuso. | Full Resin version: new LED and circuit encapsulation technology that extends product life. Features diffused glass. | Version Full Resin: nouvelle technologie d'encapsulation des LED et circuit électronique qui prolonge la durée de vie du produit. Comprend un verre diffus. | Versión Full Resin: nueva tecnología de encapsulación de LED y circuitos electrónicos que prolongan la vida útil del producto. Incorpora cristal difuso.

