


CNC 50 Top 2L

IP67 IK 10 20J xx9 CE UK CA 2000 KG MAX 65°C MAX	LED		COL.		CODE *
	W	LM	REAL LM		
	6,5	650	453	⊠ ⊗	500mA-14V
6,5	650	453	⊠ ⊗	24V	LL107021□




24V:
Fino ad esaurimento.
Until our stock lasts.
Jusqu'à épuisement de stock.
Hasta el agotamiento del stock.

★ Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Versione ghiera con 2 aperture da 110°. | Version with Top retaining ring with two 110° openings. | Version avec virole Top 2 ouvertures à 110°. | Versión casquillo Top con 2 aperturas de 110°.

CNC 50 Swing

IP67 IK 07 2J xx5 CE UK CA 65°C MAX	LED		COL.		CODE *
	W	LM	REAL LM		
	6,5	650	Max 427	⊠ ⊗	500mA-14V
6,5	650	Max 427	⊠ ⊗	24V	LL107013□ LL107046□ LL107047□




Fino ad esaurimento.
Until our stock lasts.
Jusqu'à épuisement de stock.
Hasta el agotamiento del stock.

★ Complete the CODE ○ OPTIC S | 13° M | 24° L | 53° D | Diff. □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Versione orientabile. Picchetto non incluso. | Swivel version. Stake not included. | Version orientable. Piquet non compris. | Versión orientable. Piquete no incluido.

CNC 50 Swing Spot

IP67 IK 07 2J xx5 CE UK CA 65°C MAX	LED		COL.		CODE *
	W	LM	REAL LM		
	6,5	650	Max 488	⊠ ⊗	500mA-14V
6,5	650	Max 488	⊠ ⊗	24V	LL107031□



Fino ad esaurimento.
Until our stock lasts.
Jusqu'à épuisement de stock.
Hasta el agotamiento del stock.

★ Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Versione orientabile antiabbagliamento. Picchetto non incluso. | Adjustable anti-glare version. Stake not included. | Version orientable antiéblouissement. Piquet non compris. | Versión orientable antiencandilamiento. Estaca no incluida.