







CNC 99 CL

IP67 IK 10 20J xx9 2000 ^{KG} _{MAX} 53 ^{°C} _{MAX} CE UK ER	LED			COL.	CODE *	
	W	LM	REAL LM			
	5	470	45	 	<input type="checkbox"/> LL137000 <input type="checkbox"/> LL13700W <input type="checkbox"/> LL13700G <input type="checkbox"/> LL13700E <input type="checkbox"/> LL13700K	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Tutti i modelli, se installati con armatura cod. LB1230001, diventano calpestabile. Cod. LL137000N/3/2 ghiera in acciaio inox. | When installed with recess box code LB1230001, all models are walk-over. Cod. LL137000N/3/2 stainless steel retaining ring. | Tous les modèles, lorsqu'ils sont installés avec le code d'armure LB1230001, deviennent praticables. Cod. LL137000N/3/2 collerette en acier inox. | Todos los modelos, cuando se instalan con la caja de empotrar cod. LB1230001, se vuelven transitables. Cod. LL137000N/3/2 casquillos de acero inoxidable.




CNC 99 C2L

IP67 IK 10 20J xx9 2000 ^{KG} _{MAX} 53 ^{°C} _{MAX} CE UK ER	LED			COL.	CODE *	
	W	LM	REAL LM			
	5	470	100	 	<input type="checkbox"/> LL137010 <input type="checkbox"/> LL13701W <input type="checkbox"/> LL13701G <input type="checkbox"/> LL13701E <input type="checkbox"/> LL13701K	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Tutti i modelli, se installati con armatura cod. LB1230001, diventano calpestabile. Cod. LL137010N/3/2 ghiera in acciaio inox. | Bidirectional version. When installed with recess box code LB1230001, all models are walk-over. Cod. LL137010N/3/2 stainless steel retaining ring. | Tous les modèles, lorsqu'ils sont installés avec le code d'armure LB1230001, deviennent praticables. Cod. LL137010N/3/2 collerette en acier inox. | Todos los modelos, cuando se instalan con la caja de empotrar cod. LB1230001, se vuelven transitables. Cod. LL137010N/3/2 casquillos de acero inoxidable.




CNC 99 C4L

IP67 IK 10 20J xx9 2000 ^{KG} _{MAX} 53 ^{°C} _{MAX} CE UK ER	LED			COL.	CODE *	
	W	LM	REAL LM			
	5	470	200	 	<input type="checkbox"/> LL137020 <input type="checkbox"/> LL13702W <input type="checkbox"/> LL13702G <input type="checkbox"/> LL13702E <input type="checkbox"/> LL13702K	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Tutti i modelli, se installati con armatura cod. LB1230001, diventano calpestabile. Cod. LL137020N/3/2 ghiera in acciaio inox. | When installed with recess box code LB1230001, all models are walk-over. Cod. LL137020N/3/2 stainless steel retaining ring. | Tous les modèles, lorsqu'ils sont installés avec le code d'armure LB1230001, deviennent praticables. Cod. LL137020N/3/2 collerette en acier inox. | Todos los modelos, cuando se instalan con la caja de empotrar cod. LB1230001, se vuelven transitables. Cod. LL137020N/3/2 casquillos de acero inoxidable.

CNC 99 C180

IP67 IK 10 20J xx9 2000 ^{KG} _{MAX} 53 ^{°C} _{MAX} CE UK ER	LED			COL.	CODE *	
	W	LM	REAL LM			
	5	470	93	 	<input type="checkbox"/> LL137030 <input type="checkbox"/> LL13703W <input type="checkbox"/> LL13703G <input type="checkbox"/> LL13703E <input type="checkbox"/> LL13703K	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Versione a 180°. Tutti i modelli, se installati con armatura cod. LB1230001, diventano calpestabile. Cod. LL137030N/3/2 ghiera in acciaio inox. | 180° version. When installed with recess box code LB1230001, all models are walk-over. Cod. LL137030N/3/2 stainless steel retaining ring. | Version 180°. Tous les modèles, lorsqu'ils sont installés avec le code d'armure LB1230001, deviennent praticables. Cod. LL137030N/3/2 collerette en acier inox. | Versión 180°. Todos los modelos, cuando se instalan con la caja de empotrar cod. LB1230001, se vuelven transitables. Cod. LL137030N/3/2 casquillos de acero inoxidable.