


Delta 1 Simmetrico



IP66 IK 08 5J xx7 CE UK	LED			COL.	CODE *	
	W	LM	REAL LM			
	MAX.	MAX.			LL15411WS1□	
	37	6237	5800	220-240 V		LL15411GS1□
						LL15411KS1□
						LL15411BS1□
						LM15411WS1□
	37	6237	5800	220-240 V DALI		LM15411GS1□
						LM15411KS1□
						LM15411BS1□
						LL15412WS1□
	50	7489	6965	220-240 V		LL15412GS1□
						LL15412KS1□
						LL15412BS1□
						LM15412WS1□
	50	7489	6965	220-240 V DALI		LM15412GS1□
						LM15412KS1□
						LM15412BS1□
						LS15411WS1□
	17	3175	2953	220-240 V (☞)		LS15411GS1□
						LS15411KS1□
						LS15411BS1□
						LS15412WS1□
	27	4372	4066	220-240 V (☞)		LS15412GS1□
						LS15412KS1□
						LS15412BS1□



* Complete the CODE □ LED COLOUR 5 | 5700K N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

Versione on-off: cavo 0,7m H05RN-F. Versione DALI: cavo 0,7m H07RN-F. | On-off version cable: 0,7m H05RN-F. Cable DALI version: 0,7m H07RN-F. | Câble version on-off : 0,7m H05RN-F. Câble version DALI : 0,7m H07RN-F. | Cable versión on-off: 0,7m H05RN-F. Cable versión DALI: 0,7m H07RN-F.