


























Delta 2 Asimmetrico

NEW

IP66 IK 08 5J xx7 CE UK CA	LED			COL.	CODE *
	W	LM MAX.	REAL LM MAX.		
●	72	12.326	11.217	⊕ ⊙ 220-240 V	 LL15421WA1□
					 LL15421GA1□
					 LL15421KA1□
					 LL15421BA1□
	72	12.326	11.217	⊕ ⊙ 220-240 V DALI	 LM15421WA1□
					 LM15421GA1□
 LM15421KA1□					
 LM15421BA1□					
97	14.670	13.350	⊕ ⊙ 220-240 V	 LL15422WA1□	
				 LL15422GA1□	
				 LL15422KA1□	
				 LL15422BA1□	
97	14.670	13.350	⊕ ⊙ 220-240 V DALI	 LM15422WA1□	
				 LM15422GA1□	
				 LM15422KA1□	
				 LM15422BA1□	
119	17.260	15.707	⊕ ⊙ 220-240 V	 LL15423WA1□	
				 LL15423GA1□	
				 LL15423KA1□	
				 LL15423BA1□	
119	17.260	15.707	⊕ ⊙ 220-240 V DALI	 LM15423WA1□	
				 LM15423GA1□	
				 LM15423KA1□	
				 LM15423BA1□	



* Complete the CODE □ LED COLOUR 5 | 5700K N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

Versione on-off: cavo 0,7m H05RN-F. Versione DALI: cavo 0,7m H07RN-F. | On-off version cable: 0,7m H05RN-F. Cable DALI version: 0,7m H07RN-F. | Câble version on-off : 0,7m H05RN-F. Câble version DALI : 0,7m H07RN-F. | Cable versión on-off: 0,7m H05RN-F. Cable versión DALI: 0,7m H07RN-F.