



















Flag 430

IP66 IK 08 5J xx7 CE UK CB	LED			COL.	CODE *	
	W	LM	REAL LM			
	MAX.					
35	4575	3420	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V	 LL14002W□□		
				 LL14002G□□		
				 LL14002E□□		
				 LL14002K□□		
35	4575	3420	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V DALI	 LM14002W□□		
				 LM14002G□□		
				 LM14002E□□		
				 LM14002K□□		

* Complete the CODE OPTIC S | Spot-32° W | Wide-95° A | Asymm.-140°X45° LED COLOUR N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K










Flag 430 Post

IP66 IK 08 5J xx7 CE UK CB	LED			COL.	CODE *	
	W	LM	REAL LM			
	MAX.					
35	4575	3420	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V	 LL14032W□□		
				 LL14032G□□		
				 LL14032E□□		
				 LL14032K□□		
35	4575	3420	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V DALI	 LM14032W□□		
				 LM14032G□□		
				 LM14032E□□		
				 LM14032K□□		

* Complete the CODE OPTIC S | Spot-32° W | Wide-95° A | Asymm.-140°X45° LED COLOUR N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

Consigliata l'installazione su pali conici Ø60. Non idoneo per pali Still. | Recommended for installation on Ø 60 conical poles. Not suitable for Still poles. | Recommandé pour l'installation sur des poteaux coniques de Ø60. Ne convient pas aux Still poteaux. | Se recomienda su instalación en postes cónicos de Ø60. No es apto para los postes Still.

Flag 430 Reg

IP66 IK 08 5J xx7 CE UK CB	LED			COL.	CODE *	
	W	LM	REAL LM			
	MAX.					
35	4575	3420	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V	 LL14012W□□		
				 LL14012G□□		
				 LL14012E□□		
				 LL14012K□□		
35	4575	3420	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V DALI	 LM14012W□□		
				 LM14012G□□		
				 LM14012E□□		
				 LM14012K□□		

* Complete the CODE OPTIC S | Spot-32° W | Wide-95° A | Asymm.-140°X45° LED COLOUR N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

Fornito con staffa a 5 step di regolazione in alluminio verniciato. | Supplied with 5-step adjustment bracket in painted aluminium. | Fourni avec un support de réglage en 5 étapes en aluminium peint. | Incluido soporte de ajuste de 5 pasos en aluminio pintado.