









Trend U&D 60 Doppio Blade

IP66 IK 07 2J xx5 CE UK ER	LED			W	LM	REAL LM	COL.	CODE *
	W	LM	REAL LM					
	6	1000	40	 220-240 V	 LL129116□			
					 LL129117□			
					 LL129118□			
					 LL129119□			
					 LL129122□			

★ Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K



Accessori | Accessories | Accessoires | Accesorios

Basamento Palo Still Ø170 mm

Basamento in nylon-fibra di vetro per palo diametro 60 mm. Adatto solo per pali STILL fino a 1500mm.

Base Ø170 mm for Still post






Fibreglass-nylon base for post diameter 60 mm. Only suitable for STILL posts up to 1500mm.


Socle Ø170 mm pour poteau Still

Socles en fibre de verre - nylon pour poteau diam.60 mm. Convient uniquement pour les poteaux STILL jusqu'à 1500mm.

Base Ø170 mm para poste Still

Base en nylon-fibra de vidrio para palo diámetro 60mm. Sólo apto para postes STILL de hasta 1500mm.

Col.	Code
	LB11812
	LB1181G
	LB1181E
	LB1181K
	LB11811



Piastra base a scomparsa - palo Still

Soluzione alternativa al tradizionale interramento o al basamento palo still mediante staffa di fissaggio a scomparsa. Consiste nell'inserire il palo still sulla staffa preforata da 3mm, realizzata in ferro zincato a caldo per immersione. Accessorio non idoneo per pali still superiori a h. 1500.

Col.	Code
	LB1130006

Retractable plate base


Alternative solution to the usual burial or to the post base using a retractable fixing bracket. The post is inserted in the 3mm pre-drilled bracket made of hot-dip zinc-coated metal. Accessory not suitable for posts higher than 1500mm.

Plaque de base rétractable

Solution alternative à l'enfouissement traditionnel ou mise en place moyennant un étrier de fixation rétractable du pieu post. Insérer le poteau Still sur l'étrier pré-percé de 3 mm, réalisé en fer galvanisé à chaud par immersion. Accessoire ne convenant pas à des poteaux Still de plus de 1500mm de haut.

Placa base oculta

Solución alternativa al entierro tradicional o a la base para palo still por medio de una brida de fijación retráctil. El palo still se introduce en la brida preagujereada de 3mm, de hierro galvanizado por inmersión. Accesorio no apto para palo still de más de 1500 mm de altura.



Dima e kit di fissaggio Palo Still

Dima, tirafondí e minuteria per ancoraggio del basamento al terreno.

Col.	Code
	LB11254

Template and fixing kit Still Post diam. 60 mm.

Template, fixing bolts and small metal parts to secure the base to the ground.

Gabarit, tire-fond et visserie pour poteau Still

Gabarit, tire-fond et visserie pour l'ancrage du socle au sol.

Plantilla y kit de fijación poste Still

Plantilla, tirafondos y tornillería para el anclaje de la base al suelo.

