



## Delta 3 Asimmetrico



IP66 IK 08 5J xx7 CE UK EBC	LED			COL.	CODE *
	W	LM MAX.	REAL LM MAX.		
	133	20.787	18.916	<b>220-240 V</b>	LL15431WA1□
					LL15431GA1□
					LL15431KA1□
					LL15431BA1□
	133	20.787	18.916	<b>220-240 V DALI</b>	LM15431WA1□
					LM15431GA1□
LM15431KA1□					
LM15431BA1□					
155	23.479	21.366	<b>220-240 V</b>	LL15432WA1□	
				LL15432GA1□	
				LL15432KA1□	
				LL15432BA1□	
155	23.479	21.366	<b>220-240 V DALI</b>	LM15432WA1□	
				LM15432GA1□	
				LM15432KA1□	
				LM15432BA1□	
196	27.799	25.297	<b>220-240 V</b>	LL15433WA1□	
				LL15433GA1□	
				LL15433KA1□	
				LL15433BA1□	
196	27.799	25.297	<b>220-240 V DALI</b>	LM15433WA1□	
				LM15433GA1□	
				LM15433KA1□	
				LM15433BA1□	



\* Complete the CODE □ LED COLOUR 5 | 5700K N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

Versione on-off: cavo 0,7m H05RN-F. Versione DALI: cavo 0,7m H07RN-F. | On-off version cable: 0,7m H05RN-F. Cable DALI version: 0,7m H07RN-F. | Câble version on-off : 0,7m H05RN-F. Câble version DALI : 0,7m H07RN-F. | Cable versión on-off: 0,7m H05RN-F. Cable versión DALI: 0,7m H07RN-F.