


## Flag 330


IP66 IK 07 2J xx5 CE UK CB	LED			COL.	CODE *
	W	LM	REAL LM MAX.		
	19	2850	1980	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V	<input type="checkbox"/> LL14000W
					<input type="checkbox"/> LL14000G
					<input type="checkbox"/> LL14000E
					<input type="checkbox"/> LL14000K
	19	2850	1980	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V DALI	<input type="checkbox"/> LM14000W
					<input type="checkbox"/> LM14000G
					<input type="checkbox"/> LM14000E
					<input type="checkbox"/> LM14000K
	19	2850	1980	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 24V	<input type="checkbox"/> LT14000W
					<input type="checkbox"/> LT14000G
					<input type="checkbox"/> LT14000E
					<input type="checkbox"/> LT14000K



\* Complete the CODE     OPTIC   S | 30°   W | Wide   A | Asymm.   D | Diff.    LED COLOUR   N | 4000K   3 | 3000K   2 | 2700K   1 | 2200K

## Flag 330 Post

IP66 IK 07 2J xx5 CE UK CB	LED			COL.	CODE *
	W	LM	REAL LM MAX.		
	19	2850	1980	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V	<input type="checkbox"/> LL14030W
					<input type="checkbox"/> LL14030G
					<input type="checkbox"/> LL14030E
					<input type="checkbox"/> LL14030K
	19	2850	1980	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V DALI	<input type="checkbox"/> LM14030W
					<input type="checkbox"/> LM14030G
					<input type="checkbox"/> LM14030E
					<input type="checkbox"/> LM14030K
	19	2850	1980	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 24V	<input type="checkbox"/> LT14030W
					<input type="checkbox"/> LT14030G
					<input type="checkbox"/> LT14030E
					<input type="checkbox"/> LT14030K



\* Complete the CODE     OPTIC   S | 30°   W | Wide   A | Asymm.   D | Diff.    LED COLOUR   N | 4000K   3 | 3000K   2 | 2700K   1 | 2200K

Fornito con adattatore per installazione su palo standard Ø60mm. | Supplied with adapter for installation on a standard Ø60 mm post. | Fourni avec adaptateur pour installation sur poteau standard Ø60 mm. | Adaptador para la instalación sobre palo estándar de Ø60 mm incluido.