

Beta 4



IP66 IK 07 2J xx5 CE UK CA	LED			COL.	CODE *
	W	LM	REAL LM		
	MAX.	MAX.			
60	11.991	10.560	⊕ 220-240 V		LL16011W□□
					LL16011G□□
60	11.991	10.560	⊕ 220-240 VAC 198-280 VDC DALI		LM16011W□□
					LM16011G□□
60	11.991	10.560	⊕ 220-240 VAC 198-280 VDC DALI		LM16011K□□
					LM16011B□□
90	16.400	14.443	⊕ 220-240 V		LL16012W□□
					LL16012G□□
90	16.400	14.443	⊕ 220-240 V		LL16012K□□
					LL16012B□□
90	16.400	14.443	⊕ 220-240 VAC 198-280 VDC DALI		LM16012W□□
					LM16012G□□
90	16.400	14.443	⊕ 220-240 VAC 198-280 VDC DALI		LM16012K□□
					LM16012B□□
130	22.730	20.017	⊕ 220-240 V		LL16013W□□
					LL16013G□□
130	22.730	20.017	⊕ 220-240 V		LL16013K□□
					LL16013B□□
130	22.730	20.017	⊕ 220-240 VAC 198-280 VDC DALI		LM16013W□□
					LM16013G□□
130	22.730	20.017	⊕ 220-240 VAC 198-280 VDC DALI		LM16013K□□
					LM16013B□□
190	30.200	26.596	⊕ 220-240 V		LL16014W□□
					LL16014G□□
190	30.200	26.596	⊕ 220-240 V		LL16014K□□
					LL16014B□□
190	30.200	26.596	⊕ 220-240 VAC 198-280 VDC DALI		LM16014W□□
					LM16014G□□
190	30.200	26.596	⊕ 220-240 VAC 198-280 VDC DALI		LM16014K□□
					LM16014B□□

