










Pin Q Asimmetrico

IP66 IK 07 2J xx5 CE UK ER	LED			COL.	CODE *
	W	LM	REAL LM		
	2	200	67	⊕ ⊙ AC DIRECT	 LL125012□
					 LL125013□
					 LL125014□
					 LL125015□
	2	200	67	⊕ ⊙ AC DIRECT Ⓚ KIT BOX	 LL125112□
					 LL125113□
					 LL125114□
					 LL125115□



* Complete the CODE □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Deflettore in alluminio. Codici LL12511: KIT composto da Pin Q Asimmetrico + armatura da incasso 502 LB1250001. | Deflector made of aluminum. Codes LL12511: Kit consisting of Pin Q Asimmetrico + recess box 502 LB1250001. | Réflecteur en aluminium. Codes LL12510, LL12511: Kit composé des Pin Q Asimmetrico + armature à encastrer 502 LB1250001. | Reflector de aluminio. Códigos LL12511: Kit compuesto por Pin Q Asimmetrico + LB1250001.

Accessori | Accessories | Accessoires | Accesorios


Scatola incasso standard 502

Recess Box 502

Armature à encastrer standard 502

Caja de empotrar standard 502

Col. Code
LB1250001



Scatola incasso standard cartongesso 502

Se utilizzata per l'installazione di PIN, il prodotto risulterà staccato dalla parete di circa 2mm.

Recess Plasterboard wall Box 502

If used for PIN installation, the product will be detached from the wall by approximately 2mm.


Armature à encastrer placoplâtre 502

Si'il est utilisé pour une installation PIN, le produit se détachera du mur d'environ 2 mm.

Caja de empotrar estándar 502 para cartón yeso

Si se utiliza para la instalación con PIN, el producto se despegará de la pared aproximadamente 2 mm.

Col. Code
LB11693



Bus DALI

Varialuce universale comandabile con segnale DALI. Dimmerazione a Taglio di Fase discendente (a fine fase) IGBT Trailing-Edge.

Bus DALI

Universal dimmer controlled by DALI signal. Descending Phase Cutting dimming (at the end of the phase) IGBT Trailing-Edge.

Bus DALI

Variateur universel commandé par un signal DALI. Phase descendante Gradation par coupure (à la fin de la phase) IGBT Trailing-Edge.

Bus DALI

Dimmer universal controlado por señal DALI. Atenuación por corte de fase descendente (al final de la fase) IGBT Trailing-Edge.

Col. Code
LB1070110

