

Stile Next 106L Asimmetrica

IP66 IK 06 1J xx3 CE UK CB	LED			COL.	CODE *
	W	LM	REAL LM		
	3	310	38	  220-240 V	 LL664C□



* Complete the CODE LED COLOUR N | 4000K 3 | 3000K

Predisposto per doppio ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB44100. | Double cable entries at the back. Reflector made of EN-AB44100 die-cast aluminium primary alloy. | Possibilit  alimentazione double entr e. R flecteur en aluminium primaire inject  EN-AB44100. | Preparado para doble entrada de alimentaci n. Reflector de fundici n de aluminio primario EN-AB44100.

Stile Next 106L Asimmetrica Orizzontale

IP66 IK 06 1J xx3 CE UK CB	LED			COL.	CODE *
	W	LM	REAL LM		
	4	490	70	  220-240 V	 LL666F□




* Complete the CODE LED COLOUR N | 4000K 3 | 3000K

Predisposto per doppio ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB44100. | Double cable entry at the back. Reflector made of EN-AB44100 die-cast aluminium primary alloy. | Possibilit  alimentation double entr e. R flecteur en aluminium primaire inject  EN-AB44100. | Preparado para doble entrada de alimentaci n. Reflector de fundici n de aluminio primario EN-AB44100.

Stile Next 106E

IP66 IK 06 1J xx3 CE UK CB	LED			COL.	CODE *
	W	LM	REAL LM		
	6	720	283	  220-240 V	 LL652D□
	6	720	283	  24V	 LL653D□



* Complete the CODE LED COLOUR N | 4000K 3 | 3000K

Predisposto per doppio ingresso alimentazione. LL653DN/3 alimentatore escluso. | Double cable entry at the back. LL653DN/3 ballast not included. | Possibilit  alimentation double entr e. LL653DN/3 ballast exclus. | Preparado para doble entrada de alimentaci n. LL653DN/3 Alimentador no incluido.