
























Trend U&D 220

IP66 IK 10 20J xx9 CE UK CA	LED			COL.	POLIGLASS	TRASP.	
	W	LM	REAL LM		CODE *	CODE *	
	24	3600	2160-3310	⊕ ⊙ 220-240 V		LL490008 □	LL490012 □
						LL490009 □	LL490013 □
						LL490010 □	LL490014 □
						LL490011 □	LL490015 □
						LL490024 □	LL490020 □
	15	2200	1260-2060	⊕ ⊙ 220-240 V		LL4921 □	LL4951 □
						LL492G □	LL495G □
						LL492E □	LL495E □
						LL492K □	LL495K □
						LL492B □	LL495B □
	11	1400	1078	⊕ ⊙ 220-240 V			LL4961 □
							LL496G □
							LL496E □
							LL496K □
							LL496B □
LAMP							
	ATT. MAX	CFL					
E27	1x20				LB49221	LB49521	
					LB4922G	LB4952G	
					LB4922E	LB4952E	
					LB4922K	LB4952K	
					LB4922B	LB4952B	



* Complete the CODE ○ OPTIC S | 8° M | 11° L | 30° □ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Lampade dim. max: E27 128 mm Ø 48 mm. BORDO MARE: aggiungi S alla fine del codice selezionato comprensivo di colore LED per avere il prodotto fornito con trattamento bordo mare contro le nebbie saline. | Lamp max. dim.: E27 128 mm Ø 48 mm. BORDO MARE: add S to the end of the selected code including LED colour to have the product supplied with sea treatment against salt spray. | Lampes dim. max: E27 128 mm Ø 48 mm. BORDO MARE: ajoutez S à la fin du code sélectionné, y compris la couleur LED, pour que le produit soit fourni avec un traitement de bord de mer contre le brouillard salin. | Dim. máx. lámparas: E27 128 mm. Ø 48 mm. BORDO MARE: añade S al final del código seleccionado incluyendo el color LED para que el producto se suministre con tratamiento marino contra la niebla salina.