














CNC 99 C Up

IP67 IK 10 20J xx9 ↓ 500 KG MAX ↑ 53°C MAX CE UK CR	LED			COL. CODE *  LL137040□  LL13704W□  LL13704G□  LL13704E□  LL13704K□	 × 24V	
	W	LM	REAL LM			
	5	470	173			

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Cod. LL137040N/3/2 ghiera in acciaio inox. Diffusore in policarbonato, effetto poliGLASS. | Cod. LL137040N/3/2 stainless steel retaining ring. Polycarbonate diffuser, polyGLASS effect. | Cod. LL137040N/3/2 collerette en acier inox. Diffuseur en polycarbonate, effet polyGLASS. | Cod. LL137040N/3/2 casquillos de acero inoxidable. Difusor de policarbonato, efecto polyGLASS.







CNC 99 QL

IP67 IK 10 20J xx9 ↓ 2000 KG MAX ↑ 53°C MAX CE UK CR	LED			COL. CODE *  LL13710W□  LL13710G□  LL13710E□  LL13710K□	 × 24V	
	W	LM	REAL LM			
	5	470	52			

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Tutti i modelli, se installati con armatura cod. LB1230001, diventano calpestabile. | When installed with recess box code LB1230001, all models are walk-over. | Tous les modèles, lorsqu'ils sont installés avec le code d'armure LB1230001, deviennent praticables. | Todos los modelos, cuando se instalan con la caja de empotrar cod. LB1230001, se vuelven transitables.







CNC 99 Q2L

IP67 IK 10 20J xx9 ↓ 2000 KG MAX ↑ 53°C MAX CE UK CR	LED			COL. CODE *  LL13711W□  LL13711G□  LL13711E□  LL13711K□	 × 24V	
	W	LM	REAL LM			
	5	470	98			

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Tutti i modelli, se installati con armatura cod. LB1230001, diventano calpestabile. | When installed with recess box code LB1230001, all models are walk-over. | Tous les modèles, lorsqu'ils sont installés avec le code d'armure LB1230001, deviennent praticables. | Todos los modelos, cuando se instalan con la caja de empotrar cod. LB1230001, se vuelven transitables.

CNC 99 Q4L

IP67 IK 10 20J xx9 ↓ 2000 KG MAX ↑ 53°C MAX CE UK CR	LED			COL. CODE *  LL13712W□  LL13712G□  LL13712E□  LL13712K□	 × 24V	
	W	LM	REAL LM			
	5	470	170			

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Tutti i modelli, se installati con armatura cod. LB1230001, diventano calpestabile. | When installed with recess box code LB1230001, all models are walk-over. | Tous les modèles, lorsqu'ils sont installés avec le code d'armure LB1230001, deviennent praticables. | Todos los modelos, cuando se instalan con la caja de empotrar cod. LB1230001, se vuelven transitables.