



























Delta 1 Asimmetrico



IP66 IK 08 5J xx7 CE UK CB	LED			COL.	CODE *
	W	LM MAX.	REAL LM MAX.		
	37	6237	5676	⊕ ✓ 220-240 V	 LL15411WA1□
					 LL15411GA1□
					 LL15411KA1□
					 LL15411BA1□
	37	6237	5676	⊕ ✓ 220-240 V DALI	 LM15411WA1□
					 LM15411GA1□
					 LM15411KA1□
					 LM15411BA1□
	50	7489	6815	⊕ ✓ 220-240 V	 LL15412WA1□
					 LL15412GA1□
					 LL15412KA1□
					 LL15412BA1□
50	7489	6815	⊕ ✓ 220-240 V DALI	 LM15412WA1□	
				 LM15412GA1□	
				 LM15412KA1□	
				 LM15412BA1□	
17	3175	2889	⊕ ✓ 220-240 V (☞)	 LS15411WA1□	
				 LS15411GA1□	
				 LS15411KA1□	
				 LS15411BA1□	
27	4372	3979	⊕ ✓ 220-240 V (☞)	 LS15412WA1□	
				 LS15412GA1□	
				 LS15412KA1□	
				 LS15412BA1□	



* Complete the CODE □ LED COLOUR 5 | 5700K N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

Versione on-off: cavo 0,7m H05RN-F. Versione DALI: cavo 0,7m H07RN-F. | On-off version cable: 0,7m H05RN-F. Cable DALI version: 0,7m H07RN-F. | Câble version on-off : 0,7m H05RN-F. Câble version DALI : 0,7m H07RN-F. | Cable versión on-off: 0,7m H05RN-F. Cable versión DALI: 0,7m H07RN-F.