



Delta 3 Simmetrico



IP66 IK 08 5J xx7 CE UK ER	LED			COL.	CODE *
	W	LM MAX.	REAL LM MAX.		
	133	20.787	19.332	220-240 V	LL15431WS1□
					LL15431GS1□
					LL15431KS1□
					LL15431BS1□
	133	20.787	19.332	220-240 V DALI	LM15431WS1□
					LM15431GS1□
LM15431KS1□					
LM15431BS1□					
155	23.479	21.835	220-240 V	LL15432WS1□	
				LL15432GS1□	
				LL15432KS1□	
				LL15432BS1□	
155	23.479	21.835	220-240 V DALI	LM15432WS1□	
				LM15432GS1□	
				LM15432KS1□	
				LM15432BS1□	
196	27.799	25.853	220-240 V	LL15433WS1□	
				LL15433GS1□	
				LL15433KS1□	
				LL15433BS1□	
196	27.799	25.853	220-240 V DALI	LM15433WS1□	
				LM15433GS1□	
				LM15433KS1□	
				LM15433BS1□	



* Complete the CODE □ LED COLOUR 5 | 5700K N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

Versione on-off: cavo 0,7m H05RN-F. Versione DALI: cavo 0,7m H07RN-F. | On-off version cable: 0,7m H05RN-F. Cable DALI version: 0,7m H07RN-F. | Câble version on-off : 0,7m H05RN-F. Câble version DALI : 0,7m H07RN-F. | Cable versión on-off: 0,7m H05RN-F. Cable versión DALI: 0,7m H07RN-F.