



















Dodo 60

IP54 IK 10 20J xx9 	LED			COL. CODE *	
	W	LM	REAL LM		
	3	360	120	 AC DIRECT	 LL14301W□
					 LL14301L□
					 LL14301D□
					 LL14301Z□
					 LL14301B□

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Fasci disponibili: 15°, 30°, 60°, regolabili tramite mascherine sostituibili. | Available light beams: 15°, 30°, 60°, adjustable with removable masks. | Faisceaux disponibles : 15°, 30°, 60°, réglables avec masques amovibles. | Haces disponibles: 15°, 30°, 60°, ajustables mediante máscaras intercambiables.

Dodo 60 Full

IP54 IK 10 20J xx9 	LED			COL. CODE *	
	W	LM	REAL LM		
	3	360	83	 AC DIRECT	 LL14302W□
					 LL14302L□
					 LL14302D□
					 LL14302Z□
					 LL14302B□

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

Fasci disponibili: 15°, 30°, 60°, regolabili tramite mascherine sostituibili. | Available light beams: 15°, 30°, 60°, adjustable with removable masks. | Faisceaux disponibles : 15°, 30°, 60°, réglables avec masques amovibles. | Haces disponibles: 15°, 30°, 60°, ajustables mediante máscaras intercambiables.

Accessori | Accessories | Accessoires | Accesorios

Bus DALI

Variatore universale comandabile con segnale DALI. Dimmerazione a Taglio di Fase discendente (a fine fase) IGBT Trailing-Edge.

Col.	Code
	LB1070110

Bus DALI

Universal dimmer controlled by DALI signal. Descending Phase Cutting dimming (at the end of the phase) IGBT Trailing-Edge.

Bus DALI

Variateur universel commandé par un signal DALI. Phase descendante Gradation par coupure (à la fin de la phase) IGBT Trailing-Edge.

Bus DALI

Dimmer universal controlado por señal DALI. Atenuación por corte de fase descendente (al final de la fase) IGBT Trailing-Edge.

