


## Flag 200


IP66 IK 07 2J xx5 CE UK CB	LED			COL.	CODE *
	W	LM	REAL LM MAX.		
	10	1350	855	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V	<input type="checkbox"/> LL14001W
					<input type="checkbox"/> LL14001G
					<input type="checkbox"/> LL14001E
					<input type="checkbox"/> LL14001K
	10	1350	855	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V DALI	<input type="checkbox"/> LM14001W
					<input type="checkbox"/> LM14001G
					<input type="checkbox"/> LM14001E
					<input type="checkbox"/> LM14001K
	10	1350	855	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 24V	<input type="checkbox"/> LT14001W
					<input type="checkbox"/> LT14001G
					<input type="checkbox"/> LT14001E
					<input type="checkbox"/> LT14001K



\* Complete the CODE     OPTIC S | 30° W | Wide A | Asymm. D | Diff.     LED COLOUR N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

## Flag 200 Post

IP66 IK 07 2J xx5 CE UK CB	LED			COL.	CODE *
	W	LM	REAL LM MAX.		
	10	1350	855	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V	<input type="checkbox"/> LL14031W
					<input type="checkbox"/> LL14031G
					<input type="checkbox"/> LL14031E
					<input type="checkbox"/> LL14031K
	10	1350	855	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 220-240 V DALI	<input type="checkbox"/> LM14031W
					<input type="checkbox"/> LM14031G
					<input type="checkbox"/> LM14031E
					<input type="checkbox"/> LM14031K
	10	1350	855	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> 24V	<input type="checkbox"/> LT14031W
					<input type="checkbox"/> LT14031G
					<input type="checkbox"/> LT14031E
					<input type="checkbox"/> LT14031K



\* Complete the CODE     OPTIC S | 30° W | Wide A | Asymm. D | Diff.     LED COLOUR N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

Fornito con adattatore per installazione su palo standard Ø60mm. | Supplied with adapter for installation on a standard Ø60 mm post. | Fourni avec adaptateur pour installation sur poteau standard Ø60 mm. | Adaptador para la instalación sobre palo estándar de Ø60 mm incluido.