



# RNC



- ↘ RNC 270
- ↘ RNC 520
- ↘ RNC 770
- ↘ RNC 1020
- ↘ RNC 2020

- ↘ RNC Slim 270
- ↘ RNC Slim 520
- ↘ RNC Slim 770
- ↘ RNC Slim 1020
- ↘ RNC Slim 2020

# RNC

## Installazione

Installation  
Installation  
Instalación

## Incasso terra

Ground recess  
Encastrement au sol  
Empotrar suelo

## Materiali

Materials  
Materiali  
Materiales

## Materiale Corpo: PMMA | Tipo di diffusore: PMMA

Material: PMMA | Diffuser type: PMMA  
Matériel du corps: PMMA | Type de diffuseur: PMMA  
Material del cuerpo: PMMA | Tipo de difusor: PMMA

## Alimentazione

Power supply  
Alimentation  
Alimentación











24V

## Versioni

Versions  
Versions  
Versiones

## Cavo Alimentazione: 1 metro H05RN-F

Power cable: 1 m H05RN-F  
Câble d'alimentation: 1 m H05RN-F  
Cable de alimentación: 1 m H05RN-F




			
<b>RNC</b> 270	<b>RNC</b> 520	<b>RNC</b> 770	<b>24V</b>
			
			
<b>RNC</b> 1020	<b>RNC</b> 2020		
			


## COLOURS



Neutral




**RNC 270**


<b>IP67</b> <b>IK 10 20J xx9</b> <small>CE UK CR ↓ ⊙ 2000 KG MAX</small> <b>35°C MAX</b>	LED				<b>24V</b>		<b>COL.</b>	<b>CODE *</b>
	W	LM	REAL LM					
	2,5	300	75				 <b>LL138000</b>	



\* Complete the CODE




 LED COLOUR N | 4000K 3 | 3000K 2 | 2700K
**RNC 520**


<b>IP67</b> <b>IK 10 20J xx9</b> <small>CE UK CR ↓ ⊙ 2000 KG MAX</small> <b>35°C MAX</b>	LED				<b>24V</b>		<b>COL.</b>	<b>CODE *</b>
	W	LM	REAL LM					
	5	600	155				 <b>LL138001</b>	



\* Complete the CODE




 LED COLOUR N | 4000K 3 | 3000K 2 | 2700K
**RNC 770**


<b>IP67</b> <b>IK 10 20J xx9</b> <small>CE UK CR ↓ ⊙ 2000 KG MAX</small> <b>35°C MAX</b>	LED				<b>24V</b>		<b>COL.</b>	<b>CODE *</b>
	W	LM	REAL LM					
	7,5	900	220				 <b>LL138002</b>	



\* Complete the CODE




 LED COLOUR N | 4000K 3 | 3000K 2 | 2700K
**RNC 1020**


<b>IP67</b> <b>IK 10 20J xx9</b> <small>CE UK CR ↓ ⊙ 2000 KG MAX</small> <b>35°C MAX</b>	LED				<b>24V</b>		<b>COL.</b>	<b>CODE *</b>
	W	LM	REAL LM					
	10	1200	300				 <b>LL138003</b>	



\* Complete the CODE

 LED COLOUR N | 4000K 3 | 3000K 2 | 2700K
**RNC 2020**

<b>IP67</b> <b>IK 10 20J xx9</b> <small>CE UK CR ↓ ⊙ 2000 KG MAX</small> <b>35°C MAX</b>	LED				<b>24V</b>		<b>COL.</b>	<b>CODE *</b>
	W	LM	REAL LM					
	20	2400	590				 <b>LL138004</b>	



\* Complete the CODE

 LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

## Chiavi di rimozione RNC

### Chiavi per rimozione apparecchio.

#### RNC removal keys

Keys for device removal

CoL. Code


LB1380000

#### Clés de retrait RNC

Clés pour retirer l'appareil

#### Llaves de extracción RNC

Llaves para extraer el aparato



## Armatura da incasso RNC 270

### Armatura da incasso in alluminio.

#### Recess box RNC 270

Aluminium recessed box.

CoL. Code


LB1380001

#### Armature à encastrer RNC 270

Armature à encastrer en aluminium.

#### Caja de empotrar RNC 270

Caja de empotrar de aluminio.



## Armatura da incasso RNC 520

### Armatura da incasso in alluminio.

#### Recess box RNC 520

Aluminium recessed box.

CoL. Code


LB1380002

#### Armature à encastrer RNC 520

Armature à encastrer en aluminium.

#### Caja de empotrar RNC 520

Caja de empotrar de aluminio.



## Armatura da incasso RNC 770

### Armatura da incasso in alluminio.

#### Recess box RNC 770

Aluminium recessed box.

CoL. Code


LB1380003

#### Armature à encastrer RNC 770

Armature à encastrer en aluminium.

#### Caja de empotrar RNC 770

Caja de empotrar de aluminio.



## Armatura da incasso RNC 1020

### Armatura da incasso in alluminio.

#### Recess box RNC 1020

Aluminium recessed box.

CoL. Code


LB1380004

#### Armature à encastrer RNC 1020

Armature à encastrer en aluminium.

#### Caja de empotrar RNC 1020

Caja de empotrar de aluminio.



## Armatura da incasso RNC 2020

### Armatura da incasso in alluminio.

#### Recess box RNC 2020

Aluminium recessed box.


#### Armature à encastrer RNC 2020

Armature à encastrer en aluminium.

#### Caja de empotrar RNC 2020

Caja de empotrar de aluminio.

CoL.	Code
	LB1380009



## Cavo H05RN-F 2x0,75

### Cavo H05RN-F in Neoprene, sezione 2x0,75. Adatto ad uso esterno.

#### Cable type H05RN-F 2x0,75

Cable type H05RN-F in Neoprene, section 2x0.75. Suitable for outdoor use.

#### Câble H05RN-F 2x0,75

Câble H05RN-F en Néoprène, section 2x0,75. Également adapté à l'usage à l'extérieur.

#### Cable H05RN-F 2x0,75

Cable H05RN-F de Neopreno, sección 2x0,75. Adecuado para el uso al exteriores.

#### Cavo H05RN-F 5m

CoL.	Code
	LB1070004

#### Cavo H05RN-F 15m


CoL.	Code
	LB1070006

#### Cavo H05RN-F 10m

CoL.	Code
	LB1070005

#### Cavo H05RN-F 20m

CoL.	Code
	LB1070007



## Alimentatore 24V in tensione costante RNC

### 24V constant voltage driver RNC

#### Alimentation à tension constante de 24V RNC

#### Alimentador de tensión constante de 24V RNC


RNC 270 / RNC Slim 270		
N° max	IP	Code
1/8	20	LB1070029
1/12	20	LB1070030
1/8	67	LB1070031
1/16	67	LB1070032
1/6 DALI	20	LB1070065
1/15 0-10V	67	LB1070113
1/15 DALI	67	LB1070114

RNC 520 / RNC Slim 520		
N° max	IP	Code
1/4	20	LB1070029
1/7	20	LB1070030
1/4	67	LB1070031
1/8	67	LB1070032
1/3 DALI	20	LB1070065
1/10 0-10V	67	LB1070113
1/10 DALI	67	LB1070114

RNC 770 / RNC Slim 770		
N° max	IP	Code
1/2	20	LB1070029
1/4	20	LB1070030
1/2	67	LB1070031
1/5	67	LB1070032
1/2 DALI	20	LB1070065
1/7 0-10V	67	LB1070113
1/7 DALI	67	LB1070114

RNC 1020 / RNC Slim 1020		
N° max	IP	Code
1/2	20	LB1070030
1/4	67	LB1070032
1 DALI	20	LB1070065
1/5 0-10V	67	LB1070113
1/5 DALI	67	LB1070114

RNC 2020 / RNC Slim 2020		
N° max	IP	Code
1	20	LB1070030
1/2	67	LB1070032
1/2 0-10V	67	LB1070113
1/2 DALI	67	LB1070114



# RNC SLIM

## Installazione

Installation  
Installation  
Instalación

## Incasso terra

Ground recess  
Encastrement au sol  
Empotrar suelo

## Materiali

Materials  
Materiali  
Materiales

## Materiale Corpo: PMMA | Tipo di diffusore: PMMA

Material: PMMA | Diffuser type: PMMA  
Matériel du corps: PMMA | Type de diffuseur: PMMA  
Material del cuerpo: PMMA | Tipo de difusor: PMMA

## Alimentazione

Power supply  
Alimentation  
Alimentación

24V

## Versioni

Versions  
Versions  
Versiones

## Cavo Alimentazione: 1 metro H05RN-F

Power cable: 1 m H05RN-F  
Câble d'alimentation: 1 m H05RN-F  
Cable de alimentación: 1 m H05RN-F

**RNC SLIM**  
270

**RNC SLIM**  
520

**RNC SLIM**  
770

**RNC SLIM**  
1020

**RNC SLIM**  
2020





**COLOURS**





Neutral

## RNC Slim 270

<b>IP67</b> <b>IK 10 20J xx9</b> <small>CE UK CR 2000 KG MAX</small> <small>35°C MAX</small>	LED				<b>COL.</b>	<b>CODE *</b>	
	W	LM	REAL LM				
	2,5	300	65	⊗			



\* Complete the CODE  LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

## RNC Slim 520

<b>IP67</b> <b>IK 10 20J xx9</b> <small>CE UK CR 2000 KG MAX</small> <small>35°C MAX</small>	LED				<b>COL.</b>	<b>CODE *</b>	
	W	LM	REAL LM				
	5	600	125	⊗			



\* Complete the CODE  LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

## RNC Slim 770

<b>IP67</b> <b>IK 10 20J xx9</b> <small>CE UK CR 2000 KG MAX</small> <small>35°C MAX</small>	LED				<b>COL.</b>	<b>CODE *</b>	
	W	LM	REAL LM				
	7,5	900	200	⊗			



\* Complete the CODE  LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

## RNC Slim 1020

<b>IP67</b> <b>IK 10 20J xx9</b> <small>CE UK CR 2000 KG MAX</small> <small>35°C MAX</small>	LED				<b>COL.</b>	<b>CODE *</b>	
	W	LM	REAL LM				
	10	1200	280	⊗			

\* Complete the CODE  LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

## RNC Slim 2020

<b>IP67</b> <b>IK 10 20J xx9</b> <small>CE UK CR 2000 KG MAX</small> <small>35°C MAX</small>	LED				<b>COL.</b>	<b>CODE *</b>	
	W	LM	REAL LM				
	20	2400	550	⊗			

\* Complete the CODE  LED COLOUR N | 4000K 3 | 3000K 2 | 2700K

## Chiavi di rimozione RNC

### Chiavi per rimozione apparecchio.

#### RNC removal keys

Keys for device removal

#### Clés de retrait RNC

Clés pour retirer l'appareil

#### Llaves de extracción RNC

Llaves para extraer el aparato

CoL.	Code
	LB1380000



## Armatura da incasso RNC Slim 270

### Armatura da incasso in alluminio.

#### Recess box RNC Slim 270

Aluminium recessed box.


#### Armature à encastrer RNC Slim 270

Armature à encastrer en aluminium.

#### Caja de empotrar RNC Slim 270

Caja de empotrar de aluminio.

CoL.	Code
	LB1380005



## Armatura da incasso RNC Slim 520

### Recess box RNC Slim 520

Aluminium recessed box.


### Armature à encastrer RNC Slim 520

Armature à encastrer en aluminium.

### Caja de empotrar RNC Slim 520

Caja de empotrar de aluminio.

CoL.	Code
	LB1380006



## Armatura da incasso RNC Slim 770

### Armatura da incasso in alluminio.

#### Recess box RNC Slim 770

Aluminium recessed box.


#### Armature à encastrer RNC Slim 770

Armature à encastrer en aluminium.

#### Caja de empotrar RNC Slim 770

Caja de empotrar de aluminio.

CoL.	Code
	LB1380007



## Armatura da incasso RNC Slim 1020

### Armatura da incasso in alluminio.

#### Recess box RNC Slim 1020

Aluminium recessed box.


#### Armature à encastrer RNC Slim 1020

Armature à encastrer en aluminium.

#### Caja de empotrar RNC Slim 1020

Caja de empotrar de aluminio.

CoL.	Code
	LB1380008





## Armatura da incasso RNC Slim 2020

### Armatura da incasso in alluminio.

#### Recess box RNC Slim 2020

Aluminium recessed box.


#### Armature à encastrer RNC Slim 2020

Armature à encastrer en aluminium.

#### Caja de empotrar RNC Slim 2020

Caja de empotrar de aluminio.

Col.	Code
	LB1380010



## Cavo H05RN-F 2x0,75

### Cavo H05RN-F in Neoprene, sezione 2x0,75. Adatto ad uso esterno.

#### Cable type H05RN-F 2x0,75

Cable type H05RN-F in Neoprene, section 2x0.75. Suitable for outdoor use.

#### Câble H05RN-F 2x0,75

Câble H05RN-F en Néoprène, section 2x0,75. Également adapté à l'usage à l'extérieur.

#### Cable H05RN-F 2x0,75

Cable H05RN-F de Neopreno, sección 2x0,75. Adecuado para el uso al exteriores.

#### Cavo H05RN-F 5m

Col.	Code
	LB1070004

#### Cavo H05RN-F 15m

Col.	Code
	LB1070006

#### Cavo H05RN-F 10m

Col.	Code
	LB1070005

#### Cavo H05RN-F 20m

Col.	Code
	LB1070007



## Alimentatore 24V in tensione costante RNC

### 24V constant voltage driver RNC

#### RNC 270 / RNC Slim 270

N° max	IP	Code
1/8	20	LB1070029
1/12	20	LB1070030
1/8	67	LB1070031
1/16	67	LB1070032
1/6 DALI	20	LB1070065
1/15 0-10V	67	LB1070113
1/15 DALI	67	LB1070114

#### RNC 770 / RNC Slim 770

N° max	IP	Code
1/2	20	LB1070029
1/4	20	LB1070030
1/2	67	LB1070031
1/5	67	LB1070032
1/2 DALI	20	LB1070065
1/7 0-10V	67	LB1070113
1/7 DALI	67	LB1070114

#### RNC 2020 / RNC Slim 2020


N° max	IP	Code
1	20	LB1070030
1/2	67	LB1070032
1/2 0-10V	67	LB1070113
1/2 DALI	67	LB1070114

#### RNC 520 / RNC Slim 520

N° max	IP	Code
1/4	20	LB1070029
1/7	20	LB1070030
1/4	67	LB1070031
1/8	67	LB1070032
1/3 DALI	20	LB1070065
1/10 0-10V	67	LB1070113
1/10 DALI	67	LB1070114

#### RNC 1020 / RNC Slim 1020

N° max	IP	Code
1/2	20	LB1070030
1/4	67	LB1070032
1 DALI	20	LB1070065
1/5 0-10V	67	LB1070113
1/5 DALI	67	LB1070114





## FEATURES

### **Rimozione RNC con apposite chiavi (non incluse)**

Remove RNC with special keys (not included)

Enlèvement du RNC avec des clés spéciales (non incluses)

Desmontaje RNC con llaves especiales (no incluidas)



RNC



RNC SLIM







RNC SLIM 1020







RNC 770



RNC 520