






Stile Next 103

IP66 IK 06 1J xx3 CE UK ER	LED			COL.	CODE *	
	W	LM	REAL LM			
	3	310	68	  220-240 V	 LL642C	
	6	720	170	  220-240 V	 LL642D	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K

Predisposto per singolo ingresso alimentazione. | Single cable entry at the back. | Entrée d'alimentation simple. | Preparado para la entrada de una única alimentación.

Stile Next 103 Asimmetrica

IP66 IK 06 1J xx3 CE UK ER	LED			COL.	CODE *	
	W	LM	REAL LM			
	3	310	45	  220-240 V	 LL644C	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K

Predisposto per singolo ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB44100. | Single cable entry at the back. Reflector made of EN-AB44100 die-cast aluminium primary alloy. | Entrée d'alimentation simple. Réflecteur en aluminium primaire injecté EN-AB44100 | Preparado para la entrada de una única alimentación. Reflector de fundición de aluminio primario EN-AB44100.

Stile Next 106L

IP66 IK 06 1J xx3 CE UK ER	LED			COL.	CODE *	
	W	LM	REAL LM			
	6	720	217	  220-240 V	 LL662D	
	6	720	217	  24V	 LL663D	

* Complete the CODE LED COLOUR N | 4000K 3 | 3000K

Predisposto per doppio ingresso alimentazione. LL663DN/3 alimentatore escluso. | Double cable entry at the back. LL663DN/3 ballast not included. | Possibilit  alimentazione double entr e. LL663DN/3 ballast exclus. | Preparado para doble entrada de alimentaci n. LL663DN/3 Alimentador no incluido.