


Time 180



IP65 IK 08 5J xx7 CE UK ER	LED			COL.	CODE *
	W	LM	REAL LM		
180°	26	2800	2500	☐ ☑ 220-240 V	● LL155180B ☐
					● LL155180G ☐
					● LL155180E ☐
					● LL155180K ☐
26	2800	2500	☐ ☑ 220-240 V DALI	● LM155180B ☐	
				● LM155180G ☐	
				● LM155180E ☐	
				● LM155180K ☐	
52	6100	4500	☐ ☑ 220-240 V	● LL155181B ☐	
				● LL155181G ☐	
				● LL155181E ☐	
				● LL155181K ☐	
52	6100	4500	☐ ☑ 220-240 V DALI	● LM155181B ☐	
				● LM155181G ☐	
				● LM155181E ☐	
				● LM155181K ☐	




* Complete the CODE ☐ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

Consigliata l'installazione su pali metallici Ø60. Non idoneo per pali Still. Cavo versione ON-OFF: 1m H05RN-F 2x1. Cavo versione DALI: 1m H07RN-F 4x1. Recommended for installation on Ø 60 metal poles. Not suitable for Still poles. Cable ON-OFF version: 1m H05RN-F 2x1. Cable DALI version: 1m H07RN-F 4x1. | Recommandé pour l'installation sur des poteaux métalliques de Ø60. Ne convient pas aux Still poteaux. Câble version ON-OFF : 1m H05RN-F 2x1. Câble version DALI : 1m H07RN-F 4x1. | Se recomienda su instalación en postes metálicos de Ø60. No es apto para los postes Still. Cable versión ON-OFF: 1m H05RN-F 2x1. Cable versión DALI: 1m H07RN-F 4x1.

Time 360



IP65 IK 08 5J xx7 CE UK ER	LED			COL.	CODE *
	W	LM	REAL LM		
360°	52	6100	5400	☐ ☑ 220-240 V	● LL155360B ☐
					● LL155360G ☐
					● LL155360E ☐
					● LL155360K ☐
52	6100	5400	☐ ☑ 220-240 V DALI	● LM155360B ☐	
				● LM155360G ☐	
				● LM155360E ☐	
				● LM155360K ☐	



* Complete the CODE ☐ LED COLOUR N | 4000K 3 | 3000K 2 | 2700K 1 | 2200K

Consigliata l'installazione su pali metallici Ø60. Non idoneo per pali Still. Cavo versione ON-OFF: 1m H05RN-F 2x1. Cavo versione DALI: 1m H07RN-F 4x1. Recommended for installation on Ø 60 metal poles. Not suitable for Still poles. Cable ON-OFF version: 1m H05RN-F 2x1. Cable DALI version: 1m H07RN-F 4x1. | Recommandé pour l'installation sur des poteaux métalliques de Ø60. Ne convient pas aux Still poteaux. Câble version ON-OFF : 1m H05RN-F 2x1. Câble version DALI : 1m H07RN-F 4x1. | Se recomienda su instalación en postes metálicos de Ø60. No es apto para los postes Still. Cable versión ON-OFF: 1m H05RN-F 2x1. Cable versión DALI: 1m H07RN-F 4x1.